

Security Cable

Catalog #S214USOR

NEC/CEC: FPLR(ETL)

CABLE CONSTRUCTION:

CENTER CONDUCTOR:

14 AWG Solid Bare Copper

INSULATION:

PVC

Nom. Wall: 0.013"

Dia. over Insulation: 0.090"

Black and Red

SHIELD:

UnShielded

JACKET:

Red PVC

Dia. over Jacket: 0.212"

Nominal Jacket Thickness: 0.015"

Center Conductor

Insulation

FR Ripcord

Jacket



MECHANICAL SPECIFICATION

CABLE WEIGHT	36.00 #/MFT
MINIMUM BEND RADIUS	2.2"
OPERATION TEMPERATURE -20°C to 75°C	

ELECTRICAL PROPERTIES:

OPERATING VOLTAGE: 300 VRMS
MAX CONDUCTOR DCR: 2.52 Ohms/MFT
CAPACITANCE: 34.0 pF/Ft. Nom.
FLAME TEST: FPLR NEC ART 760

FEATURES & BENEFITS:

Virgin materials
Footage marking
FPLP per NEC Article 760
Pure copper conductors
Custom colors, print, lengths available
(minimum order quantities apply)

APPLICATIONS:

Commercial audio
Security systems
Power limited controls
Sound & audio
Intercom/PA systems
Broadcast
Nurse call